

#### © 2013 American Foundry Society

Meets the Requirements of OSHA Standard 29 CFR 1910.1200 Hazard Communication and EPA Supplier Notification Requirements under Section 313 of the Emergency Planning and Community Right-to-Know Act. **SAFETY DATA SHEET (SDS)** 

# NICKEL-ALLOYED STEEL CASTINGS

SDS SC-000-016 Rev. 15

**DATE ISSUED** 

10/13

# SECTION 1—PRODUCT IDENTIFICATION & COMPANY INFORMATION

#### PRODUCT NAME

#### NICKEL-ALLOYED STEEL CASTINGS

OTHER DESIGNATIONS: ASTM (American Society for Testing & Materials) Specification No's., (ACI (Alloy Casting Institute) Alloy Designations—Grades)

ASTM No's. ACI ALLOY DESIGNATIONS (GRADES)

A128/A128M-84 C A217/A217M-84 WC4

A352/A352M-84 LC2, LC2-1, LC3, LC4, LC9

A487/A487M-84 10N, 11N, 12N, 13N, 16N, 7Q, 10Q, 11Q, 12Q, 13Q, 14Q

A732/A732M-84 9Q, 10Q, 11Q

A757/A757M-84 B2N, B2Q, B3N, B3Q, B4N, B4Q, C1Q

MIL-S-870B (Ships)

MIL-S-23008C HY-80, HY-100

#### PRODUCT IDENTIFICATION (Label Identifier)

MANUFACTURER'S NAME	STREET ADDRESS
EMERGENCY TELEPHONE NO.	MAILING ADDRESS
TELEPHONE NO.	CITY, STATE, ZIP CODE, COUNTRY
FAX NO.	E-MAIL ADDRESS/WEBSITE

#### RECOMMENDED USE OF CHEMICAL AND RESTRICTIONS ON USE

Solid casting; no restrictions

#### **SECTION 2—HAZARD IDENTIFICATION**

# **CLASSIFICATION**

Castings are metallic articles that do not present hazards in their original form.

# OTHER INFORMATION

- 1. Grinding castings that have not been cleaned or that contain embedded sand may generate significant amounts of dust containing crystalline silica.
- 2. Fumes from hot processes may contain other compounds with different exposure limits. Dust or fumes generated by machining, grinding, welding or thermal cutting of the casting may produce airborne contaminants. Consult Sections 3 & 8 for further information.

SECTION 3—COMPOSITION / INFORMATION ON INGREDIENTS		
CHEMICAL NAME/COMMON NAME/SYNONYM	Wt %	CAS NUMBER
Carbon (C)	0.12–1.3	7440-44-0
Chromium (Cr)	0–1.85	7440-47-3
Iron (Fe)	Remainder	7439-89-6
Manganese (Mn)	0.40-14.0	7439-96-5

Molybdenum (Mo)	0–1.20	7439-98-7
Nickel (Ni)	0–10.0	7440-02-0
Silicon (Si)	0.30-1.00	7440-21-3

# **SECTION 4—FIRST AID MEASURES**

**EYE CONTACT:** Not applicable

**SKIN CONTACT**: No special requirements

INGESTION: Not applicable
INHALATION: Not applicable

# **SECTION 5—FIREFIGHTING MEASURES**

**FLAMMABLE PROPERTIES:** Not applicable **EXTINGUISHING MEDIA:** Not applicable

PROTECTION OF FIREFIGHTERS: Not applicable

# **SECTION 6—ACCIDENTAL RELEASE MEASURES**

Not applicable

# **SECTION 7—HANDLING & STORAGE**

#### RECOMMENDED STORAGE

No special requirements

#### PROCEDURES FOR HANDLING

Proper hand and foot protection is recommended.

# SECTION 8—EXPOSURE CONTROLS/ PERSONAL PROTECTION

# **ENGINEERING CONTROLS**

None Required. There are no health hazards from castings in solid form.

SUBSTANCE	ACGIH TLV mg/m <sup>3</sup>	OSHA PEL mg/m <sup>3</sup>
Carbon (C)	N/E	N/E
Chromium (Cr)	0.5	1
Iron (Fe)	N/E	N/E
Manganese (Mn)	0.02 (R); 0.1 (I)	5 (C)
Molybdenum (Mo)	N/E	N/E
Nickel (Ni)	1.5 (I)	1
Niobium (Nb) formerly Columbium (Cb)	N/E	N/E
Silicon (Si)		
Total dust	N/E	15
Respirable dust	N/E	5

# SUPPLEMENTAL INFORMATION

Grinding castings that have not been cleaned or that contain embedded sand may generate significant amounts of dust containing crystalline silica.

Fumes from hot processes may contain other compounds with different exposure limits than those listed above. Dust or fumes generated by machining, grinding, welding or thermal cutting of the casting may produce airborne contaminants. Exposure limits for the most common contaminants are offered as reference. Please consult a competent person for guidance on exposure assessment and controls. In particular, Hexavalent Chromium is an OSHA Expanded Health Standard; refer to OSHA 29 CFR 1910.1026- Chromium (VI) for complete requirements.

	ACGIH TLV	OSHA PEL
SUBSTANCE	mg/m³	mg/m³
Chromium Compounds (as Cr)		
Chromium (II) inorganic compounds	N/E	0.5
Chromium (III) inorganic compounds	0.5	0.5
Chromium (VI) inorganic compounds, certain water insoluble	0.01	0.005
Chromium (VI) inorganic compounds, water soluble	0.05	0.005
Chromium (VI) all forms and compounds	N/E	0.005
Iron Compounds		
Iron oxide (Fe <sub>2</sub> O <sub>3</sub> ) fume	N/E	10
Iron oxide (Fe <sub>2</sub> O <sub>3</sub> )	5 (R)	N/E
Molybdenum Compounds (as Mo)		
Insoluble compounds (as Mo)	10 (I); 3 (R)	N/E
Soluble compounds (as Mo)	0.5 (R)	5
Total Dust	N/E	15
Nickel Compounds (as Ni)		
Insoluble, inorganic compounds	0.2(I)	1
Soluble, inorganic compounds	0.1(I)	1
Nickel oxide	0.2(I)	1

# **TERMS**

All exposure limits referenced above are 8 hour time weighted averages (TWA) unless otherwise noted.

N/E = None Established

C = Ceiling

I = Inhalable fractionR= Respirable fraction

TLV = Threshold Limit Value/American Conference of Industrial Hygienists (ACGIH)

PEL = Permissible Exposure Limit / OSHA

STEL= Short term exposure limit mg/m³ = milligrams per cubic meter

# PERSONAL PROTECTION

Proper hand and foot protection is recommended.

# **SECTION 9—PHYSICAL & CHEMICAL PROPERTIES**

# **APPEARANCE / PHYSICAL STATE**

Solid, silver gray in color

Cond, Silver gray in color	
ODOR/ODOR THRESHOLD	VAPOR DENSITY
None	Not applicable
MELTING POINT/FREEZING POINT	SPECIFIC GRAVITY (relative density)
2744-3199°F (1504-1704°C)	0.28 lb/in <sup>3</sup> (7.74 g/cm <sup>3</sup> ) for cast alloy steels
BOILING POINT	VAPOR PRESSURE
5000 °F (2750 °C) for iron	Not applicable
FLASH POINT	EVAPORATION RATE
Not applicable for solid castings	Not applicable
FLAMMABILITY	SOLUBILITY IN WATER
Not flammable	Insoluble
UPPER AND LOWER FLAMMABILITY LIMITS	рН
Not applicable for solid castings	Not applicable
AUTO IGNITION TEMPERATURE	VISCOSITY
Not applicable	Not applicable
DECOMPOSITION TEMPERATURE	PARTITION COEFFICIENT
Not applicable	Not applicable

SECTION 10—STABILITY & REACTIVITY		
CHEMICAL STABILITY		
Stable		
CONDITIONS TO AVOID		
None		
REACTIVITY	INCOMPATIBLE MATERIALS	
Not reactive	None	
HAZARDOUS DECOMPOSITION PRODUCTS	POSSIBILITY OF HAZARDOUS REACTIONS	
None	Not applicable	

POTENTIAL HEA	LIHEFFECIS				
EYE CONTACT:	None				
SKIN:	None				
INGESTION:	None				
INHALATION:	None				
Carcinogen Classification of Ingredients					
INGREDIENT OSHA NTP IARC TARGET ORGAN			TARGET ORGAN		
Nickel (metal)		NL	K	2B	Lung, Nose

**SECTION 11—TOXICOLOGICAL INFORMATION** 

#### **TERMS**

# OSHA—Occupational Safety & Health Administration

Y = Listed as a Human Carcinogen

# NTP—National Toxicology Program

K = Known to be a Human Carcinogen

R = Reasonably Anticipated to be a Human Carcinogen (RAHC)

# IARC—International Agency for Research on Cancer

1 = Carcinogen to Humans

2A = Probably Carcinogenic to Humans

2B = Possibly Carcinogenic to Humans

3 = Unclassifiable as to Carcinogenicity in Humans

4 = Probably not Carcinogenic to Humans

#### Other

NL = Not Listed

SECTION 12—ECOLOGICAL INFORMATION	
ECOTOXICITY PERSISTENCE AND DEGRADABILITY	
Not applicable	Not applicable
BIOACCUMULATION POTENTIAL MOBILITY IN SOIL	
Not applicable Not applicable	
OTHER ADVERSE EFFECTS	

#### OTHER ADVERSE EFFECTS

Not applicable

# SECTION 13—DISPOSAL CONSIDERATIONS

Recover or recycle if possible. Dispose of according to federal, state and local regulations. Dust collected from machining, welding, etc. may be classified as a hazardous waste. Consult federal, state and local regulations.

SECTION 14—TRANSPORT INFORMATION	
US DEPARTMENT OF TRANSPORTATION (DOT)-HMR (Hazardous Materials Registration) CANADIAN TRANSPORTATION OF DANGEROUS GOODS (TDG)	
Not Regulated Not regulated	
UN SHIPPING NAME	UN NUMBER
Not regulated	Not regulated

TRANSPORT HAZARD CLASS	PACKING GROUP
Not regulated	Not regulated
ENVIRONMENTAL HAZARDS	LABEL(S) REQUIRED?
None	No
TRANSPORT IN BULK	SPECIAL SHIPPING INFORMATION
Not applicable	Not applicable

# **SECTION 15—REGULATORY INFORMATION**

#### **US- OSHA (Hazard Communication Standard)**

Reference 29 CFR 1910.1200 and 1910.1000. A finished casting is an article as defined in the OSHA Hazard Communication Standard 29CFR 1910.1200 (c). Dust or fumes generated by cleaning, machining, grinding, or welding of the casting may produce airborne contaminants, such as chromium, iron, manganese, molybdenum, nickel, silicon, and silica.

For hexavalent chromium references see 29 CFR 1910.1026.

#### **US-EPA (Toxic Substances Control Act-TSCA)**

All components of these products are on the TSCA inventory list or are excluded from listing.

#### **US-EPA (SARA Title III)**

Releases to the environment of **Chromium, Manganese and Nickel**, may be subject to reporting under Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 72.

# **CANADA-WHMIS (Workplace Hazardous Materials Information System)**

This SDS has been prepared according to the hazard criteria of the Controlled Product Regulations (CPR) and the SDS contains the information required by the CPR.

#### **CANADA DSL (Domestic Substance List) Inventory Status**

All components of these products are on the DSL Inventory.

#### **CEPA (Canadian Environmental Protection Act)**

Chromium and nickel are on the CEPA Priorities Substances Lists

#### EINECS No. (European Inventory of Existing Commercial Chemical Substances)

All components of these products are on the EINECS list.

#### **RoHS (Restriction of Certain Hazardous Substances) Compliance**

Castings comply with RoHS

#### **CALIFORNIA PROPOSITION 65 Compliance**

WARNING: This product contains or produces chemicals known to the State of California to cause cancer and birth defects (or other reproductive harm). (California Health & Safety Code 25248.5 et seq.)

#### **US STATE REGULATORY INFORMATION**

Some of the components listed in Section 3 may be covered under specific state regulations.

SECTION 16—OTHER INFORMATION		
SDS SHEET PREPARED BY	DATE	
American Foundry Society, Inc.	10/13	
Occupational Safety & Health Committee (10-Q)		

# NOTE

This data and label information is offered in good faith as typical values and not as a product specification. No warranty either expressed or implied is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review the recommendations in specific context of the intended use and determine if they are appropriate.

Addendum: Label Information

# **PRODUCT IDENTIFIER**

SC 000-016 Rev. 15

# NICKEL-ALLOYED STEEL CASTINGS

SUPPLIER IDENTIFICATION	HAZARD PICTOGRAMS
Company Name	None*
Street Address	
Mailing Address	SIGNAL WORD
City State	None*
Zip/Postal Code Country	
Emergency Phone Number	
Other Info	
PRECAUTIONARY STATEMENTS	HAZARD STATEMENTS
None*	None*

# **OTHER INFORMATION**

- 1. Grinding castings that have not been cleaned or that contain embedded sand may generate significant amounts of dust containing crystalline silica.
- 2. Fumes from hot processes may contain other compounds with different exposure limits. Dust or fumes generated by machining, grinding, welding or thermal cutting of the casting may produce airborne contaminants. Consult Sections 3 & 8 of the SDS for further information.

<sup>\*</sup>Castings do not present hazards in their original form.